

ET Series

75-100kW | Three Phase | 8 MPPTs Hybrid Inverter (HV)

Powerful and compact, the ET Series 75-100kW hybrid inverter is a key addition to GoodWe's Commercial and Industrial (C&I) portfolio. It features an efficient DC-coupled architecture well-suited for solar-plus-storage applications. The inverter is compatible with a range of battery capacities and leverages intelligent operating modes to optimize system performance across various scenarios such as self-consumption, peak shaving, time-of-use, and grid support.



Optimized Performance

- 8 MPPTs, 200% PV oversizing
- Up to 21A per string
- 110% Unbalanced Load
- 150% AC Overloading @10s
- DC Coupling for Smarter Energy and Higher Efficiency



Flexible & Adaptable Applications

- Dual Independent Battery Inputs for More Flexible Configuration, Supporting up to 220A
- Supports ET100 with BAT100, 1C Charge and Discharge
- Generator Start-Stop Control via DI/DO Interfaces
- Seamless Backup Power with up to 200A Output



Superb Safety & Reliability

- <4ms UPS-Level Switching with STS
- Type I + II SPD on DC side¹
- Smart temp. sensing on AC and PV connectors
- Smart DC Circuit Breaker¹

Technical Data	GW75K-ET-G10	GW80K-ET-G10	GW99.99K-ET-G10	GW100K-ET-G10
Battery Side				
Battery Type			Li-Ion	
Nominal Voltage (V)			600	
Voltage Range (V)			300 ~ 800	
Start-up Voltage (V)			300	
Number of Battery Inputs			2	
Max. Continuous Charging Current (A)	85 x 2	100 x 2	110 x 2	110 x 2
Max. Continuous Discharging Current (A)	85 x 2	100 x 2	110 x 2	110 x 2
Max. Charging Power (kW)	75	88	99.99	110
Max. Discharging Power (kW)	75	88	99.99	110
PV Side				
Max. Input Power (kW)	150	160	200	200
Max. Input Voltage (V) ¹	1000	1000	1000	1000
MPPT Operating Voltage Range (V) ²	160 ~ 950	160 ~ 950	160 ~ 950	160 ~ 950
Start-up Voltage (V)			200	
Nominal Input Voltage (V)	620	620	620	620
Max. MPPT Current (A)			42 x 8	
Max. MPPT Short Circuit Current (A)			55 x 8	
Number of MPPTs			8	
Number of Strings per MPPT			2	
AC Side (on-grid)				
Nominal Power (kW)	75	80	99.99	100
Max. Power (kW)	75	88 ⁴	99.99	110 ⁴
Nominal Apparent Power from / to Grid (kVA)	75	80	99.99	100
Max. Apparent Power to Grid (kVA)	75	88 ⁵	99.99	110 ⁵
Max. Apparent Power from Grid (kVA)	75	88 ⁵	99.99	110 ⁵
Nominal Voltage (V)		220 / 380, 230 / 400, 240 / 415, 3L / N / PE		
Voltage Range (V) (according to local standard)			180 ~ 280	
Nominal Frequency (Hz)			50 / 60	
Frequency Range (Hz)			45 ~ 55 / 55 ~ 65	
Nominal Current from / to Grid (A)	114.0 @380Vac; 108.3 @400Vac; 104.4 @415Vac	121.6 @380Vac; 115.5 @400Vac; 111.3 @415Vac	152.0 @380Vac; 144.4 @400Vac; 139.2 @415Vac	152.0 @380Vac; 144.4 @400Vac; 139.2 @415Vac
Max. Current to Grid (A) ⁶	114.0 @380Vac; 108.3 @400Vac; 104.4 @415Vac	133.8 @380Vac; 127.1 @400Vac; 122.5 @415Vac	152.0 @380Vac; 144.4 @400Vac; 139.2 @415Vac	167.2 @380Vac; 158.8 @400Vac; 153.1 @415Vac
Max. Current from Grid (A) ⁶	114.0 @380Vac; 108.3 @400Vac; 104.4 @415Vac	133.8 @380Vac; 127.1 @400Vac; 122.5 @415Vac	152.0 @380Vac; 144.4 @400Vac; 139.2 @415Vac	167.2 @380Vac; 158.8 @400Vac; 153.1 @415Vac
Power Factor			0.8 leading ~ 0.8 lagging	
THDi			<3%	
Backup Side³				
Nominal Output Apparent Power (kVA)	75	80	99.99	100
Max. Output Apparent Power (kVA)	75	88	99.99	110
Peak Output Power without Grid (kW)	120% @ 60s; 150% @ 10s	110% @ continuous; 120% @ 60s; 150% @ 10s	120% @ 60s; 150% @ 10s	110% @ continuous; 120% @ 60s; 150% @ 10s
Nominal Output Voltage (V)			220 / 380, 230 / 400, 240 / 415, 3L / N / PE	
Nominal Output Frequency (Hz)			50 / 60	
Max. Output Current (A)	114.0 @380Vac; 108.3 @400Vac; 104.4 @415Vac	133.8 @380Vac; 127.1 @400Vac; 122.5 @415Vac	152.0 @380Vac; 144.4 @400Vac; 139.2 @415Vac	167.2 @380Vac; 158.8 @400Vac; 153.1 @415Vac
THDv (@Linear Load)			<3%	
On / Off-grid Switching Time			<4ms	
Generator Side³				
Nominal Apparent Power (kVA)	75	80	99.99	100
Max. Apparent Power (kVA)	75	88	99.99	110
Nominal Voltage (V)		220 / 380, 230 / 400, 240 / 415, 3L / N / PE		
Nominal Frequency (Hz)			50 / 60	
Frequency Range (Hz)			45 ~ 55 / 55 ~ 65	
Max. Current (A)	114.0 @380Vac; 108.3 @400Vac; 104.4 @415Vac	133.8 @380Vac; 127.1 @400Vac; 122.5 @415Vac	152.0 @380Vac; 144.4 @400Vac; 139.2 @415Vac	167.2 @380Vac; 158.8 @400Vac; 153.1 @415Vac
Efficiency				
Max. Efficiency	98.1%	98.1%	98.1%	98.1%
European Efficiency	97.7%	97.7%	97.7%	97.7%
Max. Battery to AC Efficiency	98.2%	98.2%	98.2%	98.2%
MPPT Efficiency			99.9%	
Protection				
PV String Current Monitoring			Integrated	
PV Insulation Resistance Detection			Integrated	
Residual Current Monitoring			Integrated	
PV Reverse Polarity Protection			Integrated	
Battery Reverse Polarity Protection			Integrated	
Anti-islanding Protection			Integrated	
AC Overcurrent Protection			Integrated	
AC Short Circuit Protection			Integrated	
AC Overvoltage Protection			Integrated	
DC Switch			Integrated	
DC Surge Protection			Type II (Type I + II Optional)	
AC Surge Protection			Type II	
AFCI ⁷			Optional	
Rapid Shutdown			Optional	
Remote Shutdown			Optional	
General Data				
Operating Temperature Range (°C)			-35 ~ +60	
Relative Humidity			0 ~ 100%	
Max. Operating Altitude (m)			4000	
Cooling Method			Smart Fan Cooling	
User Interface			LED, LCD (Optional), WLAN + APP	
Communication with BMS			CAN	
Communication			RS485, WiFi + LAN + Bluetooth, 4G + Bluetooth (Optional)	
Communication Protocols			Modbus-RTU, Modbus-TCP	
Weight (kg)			97	
Dimension (W x H x D mm)			995 x 758 x 358	
Noise Emission (dB)			<60	
Power Self-consumption at Night (W)			<15	
Ingress Protection Rating			IP66	
Anti-corrosion Class			C4	
Mounting Method			Wall Mounted	

*1: For GW75K-ET-G10/GW80K-ET-G10/GW99.99K-ET-G10/GW100K-ET-G10, when the input voltage ranges from 950V to 1000V, the inverter will enter the standby mode, and the voltage returns to 950V to enter the normal operation state.
 *2: Please refer to the user manual for the MPPT Voltage Range at nominal Power.
 *3: The STS Box or STS Cabinet is needed.
 *4: For Chile, Max. Power (kW): GW80K-ET-G10: 80kW, GW100K-ET-G10: 100kW.

*5: For Chile, Max. Apparent Power to Grid (kVA)/Max. Apparent Power from Grid (kVA): GW80K-ET-G10: 80kVA, GW100K-ET-G10: 100kVA.
 *6: For Chile, Max. Current to Grid (A)/Max. Current from Grid (A): GW80K-ET-G10: 121.6@380Vac, 115.5@400Vac, 111.3@415Vac; GW100K-ET-G10: 152.0@380Vac, 144.4@400Vac, 139.2@415Vac.
 *7: For Brazil, AFCI: Integrated.
 *: Please visit GoodWe website for the latest certificates.

GoodWe-Single page-20260227-EN-V2.1 Information may be subject to change without notice during product improving.